

## Calculating Square Footage

“My log home is around 2000 square feet. How much stain will I need?” Often that is all the information a customer has available when they first call Perma-Chink Systems. When people talk about the square footage of their home, they are usually referring to the floor area that may or may not include a garage. But does this number give us enough information to make an estimate of how much stain and topcoat will be required to finish a home? Look at the outlines of three log homes with approximately 2000 square feet of floor area on the next page. House A is just about square, House B is long and narrow and House C has two extensions on the ends. Even though the floor areas of these homes are nearly the same, the perimeters of the homes are significantly different. The perimeter is a significant factor in determining total exterior wall surface area. For example, if we have flat log walls that are 12 feet high and ignore window and door openings, the exterior wood surface area of Home A is 2136 square feet, whereas the exterior wood surface area of Home C is 2880 square feet, a difference of 35%. That is why knowing the floor area of a home does not really help us determine the amount of finish required to stain a home.

So how can you determine the square footage of your exterior log walls. It is easier to work up the numbers one wall at a time then add them together. Start by measuring the length of the wall with a tape measure. Then either measure the height or estimate it by counting the number of log courses and multiplying the number of courses by the diameter or height of the logs. Just remember that the diameter or height is in inches so you will need to convert inches into feet. For example if the logs are 6 inch high logs they are 6/12 or 0.50 feet in height and if they are 10 inch logs they are 10/12 or 0.83 feet in height. So if we have a wall that is 25 feet long and has 16 courses of 10 inch logs the calculation is:

25 ft. x 16 courses x 0.83 ft. = 332 square feet.

Now this assumes the wall is flat. What if the logs are round? A rule of thumb is to add 25% to the square footage of a wall to compensate for the increased surface area created by the curvature of the logs. So in the above example if the logs are round you would multiply the 332 square feet by 1.25 resulting in 415 square feet of wood surface area.

What about log siding? Round log siding has a curvature too, but it is typically not as pronounced as full logs. In this case, a multiplying factor of 1.15 will work.

Gable ends appear to present a challenge in calculating their square footage. Measure the height (from the base to the peak) and the width (end to end), multiply them together then divide that number by 2. This will be a good approximation.

Estimating the square footage of exterior wood surfaces is not easy and mistakes are common. Just remember a few tips; never multiply feet by inches, measure everything twice and have someone else check your calculations. We usually recommend not to deduct door and window openings (unless the windows account for over 20% of the wall area) or chink joints. It is always best to stain the log edges of a chink joint before the joint is chinked to protect the wood from water infiltration. The last thing is to add at least 10% extra product to your order. It is better to have some material left over than it is to run out towards the end of a job.

## Flat Log Walls 12 Feet High

